# Guacamole

## GuacD

Guacamole Daemon used for VNC, RDP, and SSH remotely

```
guacd:
    image: guacamole/guacd
    container_name: "guacd"
    restart: always
    networks:
      web:
        ipv4_address: 172.18.0.3
```

## Guacamole

Apache Guacamole used for VNC, RDP, and SSH remotely requires GuacD

```
guacamole:
    image: guacamole/guacamole
    container_name: "guacamole"
    restart: always
    networks:
      web:
        ipv4_address: 172.18.0.4
    links:
      - guacd
      - traefik
    environment:
      - GUACD_HOSTNAME=guacd
      - MYSQL_HOSTNAME=mysql
      - MYSQL_DATABASE=guacamole_db
      - MYSQL_USER=${USERNAME}
      - MYSQL_PASSWORD=${PASSWORD}
    labels:
      - "traefik.enable=true"
      - "traefik.http.routers.guac-web.rule=Host(`guac.kevinsloan.net`)"
      - "traefik.http.routers.guac-web.entrypoints=web"
```

```
      - "traefik.http.middlewares.add-guacamole.addprefix.prefix=/guacamole"
      - "traefik.http.routers.guac-secured.middlewares=add-guacamole"
      - "traefik.http.routers.guac-secured.rule=Host(`guac.kevinsloan.net`)"
      - "traefik.http.routers.guac-secured.entrypoints=web-secured"
```

---

Revision #2
Created 2020-05-29 01:47:09 UTC by sloan
Updated 2025-02-22 22:42:46 UTC by sloan