

Guacamole

GuacD

Guacamole Daemon used for VNC, RDP, and SSH remotely

```
guacd:
  image: guacamole/guacd
  container_name: "guacd"
  restart: always
  networks:
    web:
      ipv4_address: 172.18.0.3
```

Guacamole

Apache Guacamole used for VNC, RDP, and SSH remotely requires GuacD

```
guacamole:
  image: guacamole/guacamole
  container_name: "guacamole"
  restart: always
  networks:
    web:
      ipv4_address: 172.18.0.4
  links:
    - guacd
    - traefik
  environment:
    - GUACD_HOSTNAME=guacd
    - MYSQL_HOSTNAME=mysql
    - MYSQL_DATABASE=guacamole_db
    - MYSQL_USER=${USERNAME}
    - MYSQL_PASSWORD=${PASSWORD}
  labels:
    - "traefik.enable=true"
    - "traefik.http.routers.guac-web.rule=Host(`guac.kevinsloan.net`)"
    - "traefik.http.routers.guac-web.entrypoints=web"
    - "traefik.http.middlewares.add-guacamole.addprefix.prefix=/guacamole"
```

- "traefik.http.routers.guac-secured.middlewares=add-guacamole"
 - "traefik.http.routers.guac-secured.rule=Host(`guac.kevinsloan.net`)"
 - "traefik.http.routers.guac-secured.entrypoints=web-secured"
-

Revision #2

Created 29 May 2020 01:47:09 by sloan

Updated 22 February 2025 22:42:46 by sloan