

Radarr

radarr:

image: linuxserver/radarr

container_name: radarr

environment:

- PUID=1000
- PGID=1000
- TZ=America/New_York
- UMASK_SET=022 #optional

volumes:

- /Docker/trackers/Radarr:/config
- /drivespace/movies/movies_real:/movies
- /drivespace/movies/downloads/completed:/downloads
- /drivespace/movies/downloads/completed:/data/completed #adding this because importer was looking for

"data"

restart: unless-stopped

networks:

web:

ipv4_address: 172.18.0.8

labels:

- "traefik.enable=true"
- "traefik.http.routers.radarr-web.rule=Host(`radarr.kevinsloan.net`)"
- "traefik.http.routers.radarr-web.entrypoints=web"
- "traefik.http.routers.radarr-web.middlewares=redirect@file"
- "traefik.http.routers.radarr-secured.rule=Host(`radarr.kevinsloan.net`)"
- "traefik.http.routers.radarr-secured.entrypoints=web-secured"
- "traefik.http.routers.radarr-secured.tls.certresolver=mytlschallenge"
- "traefik.http.routers.radarr-secured.middlewares=test-auth@file"

Revision #1

Created 29 May 2020 02:01:15 by sloan

Updated 29 May 2020 02:01:30 by sloan