

Radarr

```
radarr:
  image: linuxserver/radarr
  container_name: radarr
  environment:
    - PUID=1000
    - PGID=1000
    - TZ=America/New_York
    - UMASK_SET=022 #optional
  volumes:
    - /Docker/trackers/Radarr:/config
    - /drivespace/movies/movies_real:/movies
    - /drivespace/movies/downloads/completed:/downloads
    - /drivespace/movies/downloads/completed:/data/completed #adding this because importer
was looking for "data"
  restart: unless-stopped
  networks:
    web:
      ipv4_address: 172.18.0.8
  labels:
    - "traefik.enable=true"
    - "traefik.http.routers.radarr-web.rule=Host(`radarr.kevinsloan.net`)"
    - "traefik.http.routers.radarr-web.entrypoints=web"
    - "traefik.http.routers.radarr-web.middlewares=redirect@file"
    - "traefik.http.routers.radarr-secured.rule=Host(`radarr.kevinsloan.net`)"
    - "traefik.http.routers.radarr-secured.entrypoints=web-secured"
    - "traefik.http.routers.radarr-secured.tls.certresolver=mytlschallenge"
    - "traefik.http.routers.radarr-secured.middlewares=test-auth@file"
```

Revision #1

Created 29 May 2020 02:01:15 by sloan

Updated 29 May 2020 02:01:30 by sloan